



超低温空气源高温热水机组

机组型号		ZX-DKFXRS -12II(ZGW)	ZX-DKFXRS -20II(ZGW)	ZX-DKFXRS -28II(ZGW)	ZX-DKFXRS -40II(ZGW)	ZX-DKFXRS -48II(ZGW)	ZX-DKFXRS -60II(ZGW)	ZX-DKFXRS -80II(ZGW)	ZX-DKFXRS -100II(ZGW)	ZX-DKFXRS -200II(ZGW)
匹数		3HP	5HP	7HP	10HP	12HP	15HP	20HP	25HP	50HP
电源规格		3N~/380V/50Hz								
最大功率(kW)		4.2	7.0	9.4	13.7	16.1	19.8	27.4	33.5	67.0
最大电流(A)		7.8	12.9	17.4	25.2	29.7	36.5	50.4	61.7	123.3
20℃/15℃	额定水箱温度(℃)	75℃								
	最高水箱温度(℃)	80℃								
	制热量(kW)	8.2	13.6	18.3	26.6	31.3	38.5	53.1	65.0	130.1
	产水量(L/h)	117	194	262	379	447	550	759	929	1858
	输入功率(kW)	2.7	4.5	6.1	8.9	10.4	12.8	17.7	21.7	43.4
	输入电流(A)	5.0	8.3	11.3	16.3	19.2	23.6	32.6	39.9	79.9
7℃/6℃	额定水箱温度(℃)	70℃								
	最高水箱温度(℃)	75℃								
	制热量(kW)	6.6	10.9	14.8	21.4	25.2	30.9	42.8	52.3	104.6
	产水量(L/h)	93	154	207	300	354	435	601	735	1470
	输入功率(kW)	2.6	4.4	5.9	8.6	10.1	12.4	17.1	20.9	41.9
	输入电流(A)	4.9	8.1	10.9	15.8	18.6	22.8	31.5	38.5	77.1
-12℃/-14℃	额定水箱温度(℃)	65℃								
	最高水箱温度(℃)	70℃								
	制热量(kW)	4.4	7.3	9.8	14.2	16.7	20.4	28.3	34.5	69.1
	产水量(L/h)	64	105	142	206	242	296	411	502	1004
	输入功率(kW)	2.4	3.9	5.3	7.7	9.0	11.0	15.3	18.7	37.4
	输入电流(A)	4.4	7.2	9.7	14.1	16.6	20.3	28.2	34.4	68.8
制冷剂	类型	混合								
	充注量(kg)	1.9	3.1	4.0	6.2	8.0	9.8	12.4	16.0	32.0
水流量(m ³ /h)		1.38	2.49	3.25	4.98	5.92	6.51	9.97	13.02	26.03
噪音(dB(A))		54	56	58	60	60	62	70	75	75
水侧压力损失(kPa)		35	30	40	30	40	50	40	40	40
接管尺寸(mm)		DN 25	DN 25	DN 25	DN 40	DN 40	DN 40	DN 65	DN 65	DN 80
外形尺寸	长(mm)	685	820	820	1250	1180	1180	2000	2000	2000
	宽(mm)	670	820	820	850	1060	1060	1100	1100	1920
	高(mm)	860	1180	1180	1160	1950	1950	1880	1880	1880
净重(kg)		115	150	220	350	450	480	800	900	1800

注：① 本系列产品的开发、制造遵从国标JB/T 12841-2016；

② 使用环境温度范围：-25℃-43℃；

③ 本表中的规格参数及外形尺寸因产品改良会有所变动，恕不另行通知。

变工况性能曲线

